www.helichina.com

WORLD TOP 5 CENTURY-OLD HELI





##8≝8m **(1)**

G2 series 45 t

Lithium Battery Powered Reach Stacker



- Based on mature platform, the truck needn't to make major changes to achieve "oil to electricity";
- Standardized battery pack design makes battery changing more convenient. And the battery pack has a built-in automatic fire extinguishing system;

HELI

- The traction adopts electric direct drive system, which has the advantages of high efficiency, good smoothness and high reliability.
- Double recovery of braking and telescopic luffing energy, combined with boom energy regeneration, effectively improve the service time.
- Using high-speed ratio drive axle, the motor can output greater torque power; Excellent braking performance meets the requirements of long and high frequency braking operations.
- New wide-view cab, full-suspension seats and integrated console provide comfortable driving experience;
- Digital display instrument realize real-time monitoring of vehicle status; The high-voltage electrical box comes with BMS inspection; Boom height and angle detection system improves driving stability.













Δ



Technical Data

Characteristics		
Rated capacity (the first/ second/third row)	kg	45000/31000/15000
Load center (the first/ second/third row)	mm	1965/3850/6400
Max.Lifting height(the first row)	mm	15050
Dimensions		
Overall length(with fork)	mm	11300
Overall width	mm	4148
Min.Boon height	mm	1145
Max.Boon tilting angles	0	60
Min.outside turning radius	mm	7790
Container spreader		ElME 817 INN
Side shift	mm	+800~-800
Rotation	mm	-105~+195
Battery voltage/rated capacity	V/Ah	618.24/684
Controls		Suzhou LVKON
Drive axle		Kessler





ANHUI HELI CO., LTD.

Add / No.668, FangXing Road, Hefei, China Fax / +86-551-63639966 Tel / +86-551-63639068(America); 63639258(Europe); 63639358(Asia); 63662105(Africa & Middle East)

 * Our products are subject to improvements and changes without notice.

